

Article-No.: 116417

Cyberpower PR1000ERT2U

1000VA/1000W

The Cyberpower Professional Rack/Tower Series ensures the highest quality power protection for IT equipment such as computers, workstations, servers, NAS / storage devices, network devices or telecom equipment, but also for home theater systems, multimedia devices and video surveillance systems. The UPS can be installed as rackmount or in tower design.

It uses line-interactive topology with automatic voltage regulation (AVR) and provides stabilized sine wave output power in mains and battery mode to ensure high power quality.

The output power factor of the UPS is 1, which means more devices/loads can be connected to the UPS than to UPS with lower power factor.

It has intelligent battery management technology, which helps batteries achieve longer optimized life by balancing the battery voltages of each battery. A two-phase controlled charging technology charges the batteries quickly and safely. Hot-swappable battery packs allow easy maintenance without interrupting operation.

The rotatable multifunctional matrix LCD supports intuitive operation and allows configuration of UPS options.

Via the USB interface, or optional network card, the free downloadable PowerPanel Business management software automatically communicates with the computer and safely shuts down the system in the event of a power failure. It also allows users to perform scheduled shutdowns and self-diagnostics, and monitors power consumption levels and displays approximate backup time.

XL versions allow external battery expansions to be connected to the UPS to extend run times in emergency mode.



Technical data

| | |
|--------------------------------|---|
| Name | PR1000ERT2U |
| Manufacturer | Cyberpower |
| Design | Rack (rack rails, rack angles), Tower |
| Technology | Line Interactive |
| Input voltage (Vac) | 220, 230, 240 |
| Rated input current (A) | 10 |
| Input connector type | IEC C14 |
| Power (Va) | 1000 (VA) |
| Power (Watt) | 1000 (Watt) |
| Outputs | 10 |
| Output connector type | IEC C13 |
| Switching time | 4 |
| LCD displays | Yes (Operating Mode, Power Indicator, Battery Status, Load Status, Errors & Warnings, More Information) |
| LED indicators | Yes (Operation Status, Mains Operation, Battery Operation, UPS Fault, Night Mode) |
| Emergency stop | Yes |
| Audible alarms | Yes (battery operation, low battery status, |

Highlights

- Line-interactive UPS topology
- Active PFC compatible
- Tool-less battery replacement
- High output power factor
- Overload protection
- Fast recharge technology
- Overvoltage and lightning protection
- LCD status display
- Serial communication port
- PowerPanel management software

Article-No.: 116417

Cyberpower PR1000ERT2U

1000VA/1000W

| | |
|--|--|
| | overload, overcharge, overtemperature) |
| SNMP / HTTP remote monitoring | Yes (optional RMCARD205) |
| Dimension (WxHxD) in mm | 433 x 86.5 x 412 |
| Warranty period | 3 Jahre (Batterie 3 Jahre) |