

Article-No.: 120168

Docking station Pokini Tab K10

Maximize Connectivity for Your Tablet

The Pokini Tab K10 Docking Station provides comprehensive connectivity for tablets of the 7th/8th generation. With a variety of ports, it offers maximum connectivity and flexibility for your workspace. Please note that dual monitor operation is not possible, and a separate power adapter is required, which is supplied with the tablet.

Technical data

Tablet Accessories

Ambient conditions

Power supply

manufacturer	delta electronics
form factor	outboard
type	outboard
power	65 Watt
refrigeration	unfavourable
input voltage range	100 - 240V AC V
current draw	1,5 A
efficiency level	VI
output voltage	19 V
output voltage Ampere	3,42 A
hollow plug Outer diameter	5,5 mm
hollow plug Depth	12 mm
hollow plug inner diameter	2,5 mm
plug for external power supply unit	Hollow plug 5,5mm x 2,5mm x 12mm
hollow plug Polarity	Plus inside
hollow plug angle	90°
current supply	IEC2 shaver plug
power switches	no
width	45 mm
hight	30 mm
deepth	105 mm
heart rate	50 - 60 Hz
CE	yes
CCC	yes
cUL	yes
TÜV	TÜV Rheinland
GS	Yes
RoHS	yes
EAC	ja

Housing industry (housing parts)Housing industry (housing parts)



Highlights

- Comprehensive connectivity for 7th/8th generation tablets
- Maximum connectivity and flexibility for your workspace
- Note: Dual monitor operation not supported
- Note: Compatible only with 7th/8th generation tablet CPUs

Article-No.: 120168

Docking station Pokini Tab K10

Housing part - Industry

System

Suitable for	7./8. Tablet CPU Generation
--------------	-----------------------------

Ports

Interfaces	2x USB 2.0 (right)
------------	--------------------

IO-Ports

Back Panel	2x USB 3.0, 1x RJ45 (10/100 Mbit), 1x VGA, 1x HDMI, Kensington-Lock, 1x DC-IN
------------	---

Dimensions

Dimensions (WxHxD)	180,4 x 150,7 x 76,6 mm
--------------------	-------------------------

Weight

Weight in grams	1.400
-----------------	-------

Ambient conditions