

Article-No.: 129593

Monitor 32" Curved Philips

E-Line 325E1C

Curved LCD monitor with Ultra Wide-Color | Simply immersive

The 32" curved E line display offers a truly immersive experience in a stylish design. Crystal-clear QHD with Ultra Wide-Color and AMD FreeSync technology brings your images to life!

Technical data

manufacturer	Philips
display type	VA LCD
backlight	W-LED-System
screen diagonal	31.5" (80 cm)
maximum resolution	2,560 x 1,440 pixels
aspect ratio	16:9
Screen coating	Glare-free, 3 H, gloss haze 25 %.
particularity	SmartImage, LowBlue mode, EasyRead, FreeSync, sRGB
pixel density	93 PPI
pixel spacing	0,272 mm
reaction time	4 ms
brightness	250 cd/m²
contrast (static)	3.000:1
SmartContrast	Mega Infinity DCR
SmartResponse	4 ms
viewing angle (h/v)	178
flicker-free	yes
number of colours	16.7 million.
MTBF	50.000 Hours
signal input	analogue, digital
circuit points	VGA, HDMI 1.4, DisplayPort 1.2, Audio-Out
speakers	no
Plug & Play (DDC)	DDC/CI
compatibility	DDC/CI, Mac OS X, sRGB, Windows 10/ 8.1/ 8/ 7
power supply	intramural
input voltage (power supply unit)	100 - 240V AC
power consumption during operation	40,6 Watt
height adjustable	no
pivot function	no
tiltable	yes
inclination angle	5° to 20° to
pivoting	no
VESA 100 x 100	yes
hint	VESA (100 x 100) not used by stand
safety	Kensington Lock
pedestal	Stand included in delivery
CE	yes
particularity	Lead-free, mercury-free



Highlights

- E Line
- 32 (31.5"/80 cm diag.)
- 2560 x 1440 (QHD)
- Curved display design for a more immersive experience
- Ultra Wide-Color wider range of colours for a vivid picture
- VA display delivers awesome images with wide viewing angles
- Effortlessly smooth gameplay with AMD FreeSync™ technology
- SmartContrast for rich black details
- SmartImage game mode optimised for gamers
- Cable management reduces cable clutter for a neat workspace



Article-No.: 129593

Monitor 32" Curved Philips

E-Line 325E1C

color	black
weight	7,34 kg
dimensions with base (WxHxD)	709 x 523 x 281 mm
dimensions without base (WxHxD)	709 x 425 x 88 mm
operating temperature	0°C to 40°C
storage temperature	-20°C to 60°C
operating Humidity	20% to 80% (non-condensing)
equipment	power cord, HDMI cable
guarantee	3 years on-site exchange service (handled by Philips)

