

Article-No.: 129672

Cyberpower OR600ERM1U

600VA/360W

The CyberPower Office Rackmount Series provides a simulated sine wave battery powered power supply for office system equipment such as PCs, workstations, network devices and peripherals. It is typically integrated into the office space or home office to provide a reliable uninterruptible power supply during power outages.

The UPS features a multi-function LCD display that shows real-time information such as input and output voltage levels, load and battery levels, battery life, overload warning and a sound/off mode. With RJ45 surge protection ports, the UPS prevents network devices from being exposed to sudden power surges caused by lightning, avoiding potential system damage. As for battery maintenance, the UPS enables hot-swapping of the batteries, allowing users to perform normal battery maintenance without significant interruption.

Technical data

USV

General

Name	OR600ERM1U
Manufacturer	Cyberpower
Design	Rack (rack angle)
Technology	Line Interactive
Certifications	CE, EAC, RoHS

Input

Input voltage (Vac)	230
Rated input current (A)	10
Input connector type	IEC C14

Output

Power (Va)	600 (VA)
Power (Watt)	360 (Watt)
Outputs	6
Output connector type	IEC C13

Battery

Running time at full load (min)	4
Switching time	4
Replacement battery RBP	RBP0019

Management & Communication

LCD displays	Yes (Operating Mode, Power Indicator, Battery Status, Load Status, Errors & Warnings, More Information)
LED indicators	Yes (Operation status)
HID compatible USB	1



Highlights

- Line-interactive UPS topology
- Simulated sine wave output
- Overload protection
- Overvoltage and lightning protection
- Telephone / fax / modem / DSL / network protection
- USB communication port
- SNMP / HTTP remote management capability (optional)
- Energy saving technology
- Automatic Voltage Regulation (AVR)
- Hot-swappable batteries

Article-No.: 129672

Cyberpower OR600ERM1U

600VA/360W

port

Audible alarms

Yes (Battery operation, Low battery status, Overload, UPS fault)

SNMP / HTTP remote monitoring

Yes (optional RMCARD205)

Physical size

Dimension (WxHxD) in mm

433 x 44 x 235

Warranty

Warranty period

2 years (battery 2 years)