

Article-No.: 138617

# Touch-Monitor VESA

## 21,5" Industrial

Stylish industrial display

Matching our VESA panel PCs we also offer touchmonitors without own computing power. Turn existing industrial PCs into a modern input solution, the USB touch controller is immediately recognized under current Windows and Linux operating systems.

### Technical data

#### Monitor screen

<b>manufacturer</b>	GeneralTouch
<b>panel</b>	
<b>display type</b>	TFT
<b>backlight</b>	LED
<b>screen diagonal</b>	21.5" (54.61 cm)
<b>maximum resolution</b>	1,920 x 1,080 pixels (FHD)
<b>aspect ratio</b>	16:9
<b>reaction time</b>	20 ms
<b>brightness</b>	250 cd/m²
<b>contrast (static)</b>	3.000:1
<b>viewing angle (h/v)</b>	178°/178°
<b>number of colours</b>	16.7 million.
<b>MTBF</b>	50.000 Hours

#### touch

<b>touch technology</b>	Projected capacitive touch (P-cap)
<b>usability</b>	Multi-Touch (10 fingers)
<b>usability with glove</b>	Latex glove Work glove ESD-glove
<b>touch interface</b>	USB 2.0
<b>pane</b>	antireflective glass (non glare)

#### circuit points

<b>signal input</b>	analogue, digital
<b>circuit points</b>	VGA, HDMI, DisplayPort, DVI-D
<b>VGA</b>	1
<b>DVI-D</b>	1
<b>HDMI</b>	1
<b>DisplayPort</b>	1

#### particularity

<b>speakers</b>	no
-----------------	----

#### power supply

<b>power supply</b>	outboard
<b>input voltage (power supply unit)</b>	100 - 240V AC
<b>input voltage Power supply unit from</b>	100



### Highlights

- IP65 Front
- 10-finger P-CAP Touch
- VESA mount included
- Available until 2026

Article-No.: 138617

# Touch-Monitor VESA

## 21,5" Industrial

input voltage Power supply unit up to	240
input voltage (monitor)	12V DC
power consumption during operation	20 Watt
functionalities	
height adjustable	no
VESA 75 x75	yes
VESA 100 x 100	yes
norms	
CE	CE/FCC/CCC
chassis	
housing material	aluminium
color	black/silver
weight & dimensions	
weight	6,7 kg
dimensions (WxHxD)	525.60 x 322.20 x 40.30 mm
surrounding area	
operating temperature	0°C to 40°C
storage temperature	-20°C to 60°C
operating Humidity	20% to 80% (non-condensing)
humidity (storage)	10% to 90% (non-condensing)
IP protection class (front side)	IP 65
IP protection class (rear)	IP 20
scope of supply	
equipment	PSU, VGA cable, USB cable
service	
guarantee	2 years Bring-In (LCD Panel 1 year)

