

Article-No.: 138621

Touch-Monitor Einbau

19" Industrial

Technical data

Monitor screen	
manufacturer	GeneralTouch
panel	
display type	TFT
backlight	LED
screen diagonal	19" (48 cm)
maximum resolution	1,280 x 1,024 pixels (SXGA)
aspect ratio	5:4
reaction time	5 ms
brightness	250 cd/m²
contrast (static)	1.000:1
wiewing angle (h/v)	170°/160°
number of colours	16.7 million.
touch	
touch technology	Projected capacitive touch (P-cap)
usability	Multi-Touch (10 fingers)
usability with glove	Latex glove Work glove ESD-glove
touch interface	USB 2.0
pane	antireflective glass (non glare)
circuit points	
signal input	analogue, digital
circuit points	VGA, DVI-D
VGA	1
DVI-D	1
particularity	
speakers	no
power supply	
power supply	outboard
input voltage (power supply unit)	100 - 240V AC
input voltage Power supply unit from	100
input voltage Power supply unit up to	240
input voltage (monitor)	12V DC
functionalities	
height adjustable	no

Highlights

Article-No.: 138621

Touch-Monitor Einbau

19" Industrial

VESA 75 x75	yes
VESA 100 x 100	yes
pedestal	Stand not included in delivery
norms	
CE	yes
chassis	
housing material	aluminium
color	black/silver
weight & dimensions	
weight	4,2 kg
dimensions (WxHxD)	438.7 x 363.7 x 41 mm
surrounding area	
operating temperature	0°C to 40°C
storage temperature	-20°C to 60°C
operating Humidity	20% to 80% (non-condensing)
humidity (storage)	10% to 90% (non-condensing)
IP protection class (front side)	IP 65
IP protection class (rear)	IP 20
scope of supply	
equipment	PSU, VGA cable, USB cable, mounting bracket (2x) with screws (4x)
service	
guarantee	2 years Bring-In (LCD Panel 1 year)