Article-No.: 148162

exone go Business S 1560
N5030 W11Pro

Technical data

Operating system

installed operating system	Windows® 10 Pro Value

Hard disk

memory capacity	120 GB
type	M.2 2280
interface	SATA3 with 6 Gb/s

Basic notebook system

processor

manufacturer	Intel®
label	Pentium® Silver
type	N5030
cpu socket	FCBGA1090
cores	4
threads	4
clock rate	1,10 GHz
max. clock frequency with Intel® burst frequency technology	3,10 GHz
smart cache	4 MB
bit set	64 Bit
max. TDP	6 Watt
processor graphic	Intel® UHD Graphics 605
Intel® vPro Technology	no
Intel® Hyper-Threading Technology	no
Intel® Virtualization Technology (VT-x)	yes
hint	Windows 7/8 drivers are no longer available for Intel® Gemini Lake processors.

display

display size	15.6" (39.6 cm)
display thickness	3,2 mm
max. resolution panel	1,920 x 1,080 pixels (FHD)
aspect ratio	16:9 -Format
display technology	IPS WVA
backlight	LED
display type	anti-glare

Highlights

Article-No.: 148162

exone go Business S 1560

N5030 W11Pro

contrast	500:1
brightness	220 cd/m²
reaction time	12 ms
Viewing angle	45°/40° h/v

possible memory

working memory max.	4 GB
installed memory	4 GB DDR4 SO-DIMM
hint	no memory upgrade possible

optical disc drive

optical disc drive	optional (external optical drive)

communication

WLAN	Intel® Dual Band Wireless-AC 9560, 802.11 ac
WLAN chipset	Intel® Dual Band Wireless-AC 9560
WLAN transmission standard	IEEE 802.11 a/b/g/n/ac

WiFi usage

Note for wifi usage	The range from 5150 MHz to 5350 MHz of the 5 GHz WLAN band is for indoor use only.
mobile broadband	no
bluetooth	integrated

audio/camera

audio chipset	Realtek ALC 293
sound mode	high definition
speakers	2 integrated speakers

interfaces

USB 3.2 Gen1 (5GBit/s) Type-C™	1
USB 3.2 Gen1 (5GBit/s)	1
hint	The USB 3.2 Type-C™ interface does not support charging of the notebook battery and image transfer (alternate mode) due to the PIN assignment.
USB 2.0	2
HDMI	1
audio	Audio Combo (headphones, microphone)
DC in	integrated

card reader

card reader	1x microSD
supported formats	micro SD

expansion slots

M.2 for SSD	1

exone go Business S 1560

N5030 W11Pro

hint	for M.2 SSD (2280 SATA)
M.2 for WLAN	1
advice	occupied by WLAN module

safety

Trusted Platform Module (TPM)	Firmware TPM (fTPM) im BIOS integriert
kensington lock	integrated

input devices

input devices	Keyboard with numeric keypad,\multi-touch touchpad

general

dimensions (WxHxD)	360.4 x 18.5 x 239.3 mm
weight	1,69 kg
color	black

particularity

device property	180 degree hinge

power supply

battery type	Lithium-Ionen-Polymer (embedded)
embedded battery	yes
capacity	36 WH
hint	6 months warranty on battery
battery runtime	10,5 Hours
battery runtime note	measured according to BAPCo® MobileMark® 2014 (The actual runtime depends on your hardware and software configuration)
power supply	40 Watt, external
	40 Watt, external input: 100-240V AC / 50-60Hz Output: 19V DC / 2,1A
power supply efficiency	VI
power supply connector dimensions	4,7 x 1,7 x 11 (Outside x Inside x Length)

Service

Service	2 years Pick-Up & Return

System

scope of supply	incl. battery and power supply

Additional software

additional software	free of adware, , Microsoft® Office Preload (Buy Office now, get a license right away)

Ambient conditions

Article-No.: 148162

exone go Business S 1560

N5030 W11Pro

Volume	Is your notebook too noisy for daily office use? Try the "Silent Mode" of the Control Center of your notebook. For more information, please refer to the documents under "Downloads + Links".
operating temperature	5°C to 32°C
atmospheric humidity	10% to 75% (non-condensing)

Certifications

Blue Angel	Our products meet the requirements of the Blue Angel
conformance	CE
grade	EXTRA Computer has a quality management system which is certified according to DIN ISO 9001