

Article-No.: 73580

## Cyberpower PR750ELCD

750VA/675W

The Cyberpower PR Professional Tower Series ensures the highest quality power protection for IT equipment such as computers, workstations, servers, NAS / storage devices, network devices or telecommunication devices.

It uses the line interactive topology with automatic voltage regulation (AVR) and provides stabilized sine wave output power in mains and battery mode to ensure high power quality.

Intelligent battery management checks the battery by internal resistance measurement, and can detect aging batteries and display the change request before failure. The battery compartment design with hot-swappable battery packs enables easy maintenance without interrupting operation.

The multifunctional LCD supports intuitive operation and allows configuration of UPS options.

Via the USB interface, or optional network card, the free downloadable PowerPanel Business management software automatically communicates with the computer and safely shuts down the system in the event of a power failure. It also allows users to perform scheduled shutdowns and self-diagnostics, and monitors power consumption levels and displays approximate backup time.



### Technical data

<b>Name</b>	PR750ELCD
<b>Manufacturer</b>	Cyberpower
<b>Design</b>	Tower
<b>Technology</b>	Line Interactive
<b>Input voltage (Vac)</b>	230
<b>Rated input current (A)</b>	10
<b>Input connector type</b>	IEC C14
<b>Power (Va)</b>	750 (VA)
<b>Power (Watt)</b>	675 (Watt)
<b>Outputs</b>	6
<b>Output connector type</b>	IEC C13
<b>Switching time</b>	4
<b>LCD displays</b>	Yes (Operating Mode, Power Indicator, Battery Status, Load Status, Errors & Warnings, More Information)
<b>LED indicators</b>	Yes (Operation Status, Mains Operation, Battery Operation, Wiring Fault, Change Battery)
<b>Emergency stop</b>	Yes
<b>Audible alarms</b>	Yes (Battery operation, Low battery status, Overload, UPS fault)
<b>SNMP / HTTP remote monitoring</b>	Yes (optional RMCARD205)
<b>Dimension (WxHxD) in mm</b>	136 x 162 x 349
<b>Warranty period</b>	3 Jahre (Batterie 3 Jahre)



### Highlights

- Line-interactive UPS topology
- Active PFC compatible
- Hot-swappable batteries
- EMI and RFI filters
- USB communication port
- PowerPanel management software
- Stand-alone case
- Energy saving technology
- Pure sine wave power supply
- Overload protection

Article-No.: 73580

# Cyberpower PR750ELCD

750VA/675W