

Article-No.: 73641

Cyberpower OL1500ERTXL2U

1500VA/1350W

The Cyberpower Online Eco+ series ensures the highest quality power protection for IT equipment, servers, workstations, NAS / storage devices, telecom equipment, network equipment, security / emergency systems and surveillance systems.

The UPS comes in online double conversion topology for uninterruptible power supply with additional ECO mode which provides energy saving mode to save energy cost.

The intelligent battery management checks the battery by internal resistance measurement and can detect aging batteries and display the replacement request before failure. The battery compartment design with hot-swappable battery packs allows for easy maintenance without interrupting operation. This generator-compatible UPS features the Emergency Power Off (EPO) input required in security systems, which can be used to immediately de-energize the UPS in an emergency.

To extend battery life, the UPS uses Smart Battery Management (SBM), which improves the battery charging process, extending battery life and achieving a lower total cost of ownership.

Through the USB interface, or optional network card, the free downloadable PowerPanel Business management software automatically communicates with the computer and safely shuts down the system in the event of a power failure. It also allows users to perform scheduled shutdowns and self-diagnostics, and monitors power consumption levels and displays approximate backup time.



Technical data

USV

General

Name	OL1500ERTXL2U
Manufacturer	Cyberpower
Design	Rack (rack rails, rack angles), Tower
Technology	Online double converter
Certifications	CE, C-Tick, RoHS, Active PFC Compatibility

Input

Input voltage (Vac)	200, 208, 220, 230, 240
Rated input current (A)	7.5
Input connector type	IEC C14

Output

Power (Va)	1500 (Va)
Power (Watt)	1350 (Watt)
Outputs	8
Output connector type	IEC C13

Battery

Highlights

- Online (double conversion) UPS topology
- Generator compatible
- Critical / non-critical outputs
- Intelligent Battery Management (SBM)
- External Battery Management (EBM)
- EMI and RFI filters
- LDC status display
- PowerPanel management software
- Stand-alone enclosure
- ECO operation

Article-No.: 73641

Cyberpower OL1500ERTXL2U

1500VA/1350W

Running time at full load (min)	3
Switching time	0
Replacement battery RBP	RBP0074
External battery module	BPE36V60ART2US

Management & Communication

LCD displays	Yes (Operating Mode, Power Indicator, Battery Status, Load Status, Errors & Warnings, More Information)
LED indicators	Yes (Operation Status, Mains Operation, Battery Operation, Bypass Operation, Battery Capacity, Battery Low, Overload, UPS Fault, Wiring Fault, Replace Battery)
HID compatible USB port	1
Emergency stop	Yes
Audible alarms	Yes (Battery operation, Low battery status, Overload, Overcharge, Overtemperature, UPS fault, Replace battery)
SNMP / HTTP remote monitoring	Yes (optional RMCARD205)

Physical size

Dimension (WxHxD) in mm	433 x 88 x 430
-------------------------	----------------

Warranty

Warranty period	3 Jahre (Batterie 3 Jahre)
-----------------	----------------------------