

Article-No.: 88134

# Cyberpower OL1000EXL

## 1000VA/900W

The Cyberpower Online Eco+ series ensures the highest quality power protection for IT equipment, servers, workstations, NAS / storage devices, telecom equipment, network equipment, security / emergency systems and surveillance systems.

The UPS comes in online double conversion topology for uninterruptible power supply with additional ECO mode which provides energy saving mode to save energy cost.

The intelligent battery management checks the battery by internal resistance measurement and can detect aging batteries and display the replacement request before failure. The battery compartment design with hot-swappable battery packs allows for easy maintenance without interrupting operation. This generator-compatible UPS features the Emergency Power Off (EPO) input required in security systems, which can be used to immediately de-energize the UPS in an emergency.

To extend battery life, the UPS uses Smart Battery Management (SBM), which improves the battery charging process, extending battery life and achieving a lower total cost of ownership.

Through the USB interface, or optional network card, the free downloadable PowerPanel Business management software automatically communicates with the computer and safely shuts down the system in the event of a power failure. It also allows users to perform scheduled shutdowns and self-diagnostics, and monitors power consumption levels and displays approximate backup time.

### Technical data

Name	OL1000EXL
Manufacturer	Cyberpower
Design	Tower
Technology	Online double converter
Input voltage (Vac)	200, 208, 220, 230, 240
Rated input current (A)	5
Input connector type	IEC C14
Power (Va)	1000 (VA)
Power (Watt)	900 (Watt)
Outputs	9
Output connector type	IEC C13
Switching time	0
LCD displays	Yes (Operating Mode, Power Indicator, Battery Status, Load Status, Errors & Warnings, More Information)
LED indicators	Yes (Operation Status, Mains Operation, Battery Operation, Bypass Operation, Battery Capacity, Battery Low, Overload, UPS Fault, Wiring Fault, Replace Battery)
Emergency stop	Yes
Audible alarms	Yes (Battery operation, Low battery status, Overload, Overcharge, Overtemperature, UPS fault, Replace battery)



### Highlights

- Online (double conversion) UPS topology
- Generator compatible
- Critical / non-critical outputs
- Intelligent Battery Management (SBM)
- External Battery Management (EBM)
- EMI and RFI filters
- LDC status display
- PowerPanel management software
- Stand-alone enclosure
- ECO operation

Article-No.: 88134

Cyberpower OL1000EXL

1000VA/900W

SNMP / HTTP remote monitoring	Yes (optional RMCARD205)
Dimension (WxHxD) in mm	167 x 232 x 397
Warranty period	3 Jahre (Batterie 3 Jahre)